

SMART PUBLIC DC CHARGER 150 kW, 3-phase



CONVENIENT

7' touch screen LCD for parameter browsing and setting



RELIABLE

IP54 protection for outdoor installation



GLOBAL STANDARD

OCPP v1.6 open charge point protocol. IEC 62196 type II connector



SAFE STRUCTURE

DC gun hidden design



CAPABLE

Dual CCS plug, more efficient charging



FLEXIBLE

RFID / QR (standard)
Free / APP Mega Mobility




CERTIFICATION

Certificate CE



MECHANICAL

Dimension (W/H/D) 1270 / 2110 / 910 mm
Weight < 800 KG



SMART PUBLIC DC CHARGER 150 kW, 3-phase

<p>Input & Output</p> <p>Input voltage Frequency DC plug type Output voltage range Output current Voltage accuracy Current accuracy Voltage-regulating accuracy Current-regulating accuracy Ripple coefficient Metering accuracy Efficiency Connection</p>	<p>340–460V AC 50HZ±1 CCS type II, double plugs 200-850V DC Single connector MAX:220A / per phase +0.5% ≥30A ≤ ± 1% ; < 30A: ≤ ±0.3A +0.5% ≤±1% RMS: ≤ ±0.5; Peak: ≤±1 0.5% ≥94% DC Plug *2</p>
<p>Protection</p> <p>Over voltage protection Under voltage protection Overload protection Leakage current protection Overtemperature protection Under temperature protection Surge protection</p>	<p>Yes Yes Yes Yes Yes Yes Yes</p>
<p>Function & Accessory</p> <p>Ethernet/WIFI/4G Display Indicator Payment support Emergency stop Cable Length</p>	<p>Yes / Opt / Yes 7 inch touch screen Yes RFID / QR (standard) Free / APP Mega Mobility Yes 5m</p>
<p>Working environment</p> <p>Protection degree Environment temperature Relative humidity Maximum altitude Cooling Standby power Noise emission</p>	<p>IP54 -25°C ~ +50°C 5 – 95% non-condensing <2000 m Forced air cooling <30W ≤65db</p>
<p>Mechanical</p> <p>Dimension (W / H / D) Weight</p>	<p>1270 / 2110 / 910 mm < 800 kg</p>
<p>Certification</p> <p>Certificate</p>	<p>CE</p>

